

RG/U Coax SC-Classic Series MKII; 1 x 1,02; PVC Ø 5,00 mm; black Art. No.: 600-0401LL

ANALOG

OFC



General Data

| | |
|--------------------|------------------------|
| Article number : | 600-0401LL |
| Name : | SC-Classic Series MKII |
| EAN : | 4049371003438 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Studio / Broadcast |
| Application area : | Installation |
| Application area : | ELA 100 V |
| Application : | RG/U Coax |
| Colour : | black |
| Colour detailed : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|--------------------------------------|
| Construction : | 02YSCY |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 5,00 |
| Number of Channels (video) : | 1 |
| Inner conductor (video) : | 1 |
| Inner conductor (video) [mm ²] : | 0,82 |
| Inner conductor Ø (video) [mm] : | 1,02 |
| AWG (video) : | 18 |
| Shielding : | Copper braiding tin-plated + AL-foil |
| Shielding factor [%] : | 92 |
| Copper strands (video) : | 1 |
| Copper strand Ø (video) [mm] : | 1,02 |
| Conductor insulation material : | Foam / Skin-PE |
| Conductor insulation Ø [mm] : | 2,95 |
| Weight per 1 m [g] : | 38 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,15 |
| Style variant : | round |
| Packing : | 100 m ring |
| Packing : | 500 m spool |
| Velocity factor : | 0,66 |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| RG-Type : | RG58 C/U LL |
| Width [mm] : | 5 |
| Height [mm] : | 5 |

Capacity wire/electic screen at 1m (video) [pF] : 82

Damping at 100 MHz (100m & 20° C) [dB] : 10,3

Damping at 200 MHz (100m & 20° C) [dB] : 15,2

Damping at 470 MHz (100m & 20° C) [dB] : 21,3

Damping at 862 MHz (100m & 20° C) [dB] : 31,4

Impedance [Ω] : 50

Electrical Data